

TG-15

Benchtop high speed microcentrifuge

- Frequency conversion motor drive, Microcomputer control.
- Digital display.
- Steel body, stainless steel chamber.
- Electronic lock & independent motor to control.
- 10 levels of acceleration and deceleration, 12 programs.
- Programs of RCF can be set up directly.
- Time, Speed , RCF can be modified during operation.
- Special cooling system.

Features & Advantages:

Max Speed	15000 r/min
Max RCF	21630Xg
Max Capacity	24x1.5 /2.2ml
Speed Accuracy	±20 r/min
Timer Range	1~99 min59s
Noise	≤58dB(A)
Power	AC 220V 50HZ 10A
Dimension	365x300x260 (LxWxH) mm
Weight	18 kg
Adaptor	24x0.2ml ; 24x0.5ml



TG-16S

Benchtop micro high speed centrifuge

Features:

- Brushless DC motor driving.
- Micro-computer control ,Digital display.
- Touch buttons,easy to operate.
- All-steel body,stainless steel centrifugal chamber.
- Operation parameters of instruments can be modified during operation.

Technical Parameters

Max Speed	16'000 r/min
Max RCF	17 800 Xg
Max Capacity	8X5 ml (15 000 rpm)
Speed Accuracy	±30 r/min
Timer Range	1~99min
Noise	≤60dB (A)
Power	AC 220V 50HZ 5A
Dimension	305 × 250 × 235 (L × W × H)mm
Weight	12.5 kg



Rotor Technical Data

Rotor	Capacity	Max Speed	Max RCF
NO.1 Angle Rotor	12X1.5/2.2 ml	16 000 rpm	17 800 Xg
NO.2 Angle Rotor	8X5 ml	15 000 rpm	16 380 Xg